

## Declaration of Performance

DoP Ref: 024CPR2013

Product-type: HDT/K-90


*Product intended to be used in walls and partitions*

Manufacturer	Notified Body
Keystone Lintels Ltd., Ballyreagh Business Park, Cookstown, Northern Ireland, BT80 9DG	Ceram, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ
Keystone Lintels, in accordance with the Construction Products Regulation (EU) No. 305/2011, hereby declares that product type <i>HDT/K-90</i> is manufactured to the requirements of the Harmonised European Standard EN 845-2: 2003.	Ceram No. 1289, conducted determination of the product –type.  The conformity of the product was determined as per the requirements stipulated in ZA.2 and ZA.3 of EN 845-2: 2003. The AVCP for the product is system 3.

Essential characteristics	Lintel length (mm)			hEN
	0600-1650	1800-2400	2550-3000	
Load Bearing Capacity (kN) - <i>Total UDL</i>	10	12	12	EN 845-2: 2003
<i>Figures shown are safe working loads</i>				
Deflection Under Load	Less than Effective Span/325 at maximum safe working load			
Mass Per Unit Area	NPD			
Water Absorption	Zero			
Thermal Resistance (W/mK)	50			
Resistance to Fire	NPD (Contact Keystone Technical Department for information)			
Durability (against corrosion)	L14			
Durability (against freeze/thaw)	Resistant			
Dangerous Substances	None			

Date: 30/06/2015

Issued under the sole responsibility of Keystone Lintels, signed by:



(Managing Director)