



0600-1200




Keystone Lintels Ltd.
S/K-50 215 WOL
For standard loading conditions
with 215mm wide outer leaf as
a composite beam.
To achieve loading figures lintel
must be built in with blockwork as
shown.

1350-1500




Keystone Lintels Ltd.
S/K-50 215 WOL
For standard loading conditions
with 215mm wide outer leaf as
a composite beam.
To achieve loading figures lintel
must be built in with blockwork as
shown.

1650-2100




Keystone Lintels Ltd.
S/K-50 215 WOL
For standard loading conditions
with 215mm wide outer leaf as
a composite beam.
To achieve loading figures lintel
must be built in with blockwork as
shown.

2250-2550




Keystone Lintels Ltd.
S/K-50 215 WOL
For standard loading conditions
with 215mm wide outer leaf as
a composite beam.
To achieve loading figures lintel
must be built in with blockwork as
shown.

2700-3000



Keystone Lintels Ltd.
S/K-50 215 WOL
For standard loading conditions
with 215mm wide outer leaf as
a composite beam.
To achieve loading figures lintel
must be built in with blockwork as
shown.

3150-3600



Keystone Lintels Ltd.
S/K-50 215 WOL
For standard loading conditions
with 215mm wide outer leaf as
a composite beam.
To achieve loading figures lintel
must be built in with blockwork as
shown.