0600-3000



Keystone Lintels Ltd.
X/K-70 125 WIL
For extra heavy duty loading conditions with 125mm - 150mm wide inner leaf.
To achieve loading figures, lintel must be laterally restrained.

3150-4800



Keystone Lintels Ltd.
X/K-70 125 WIL
For extra heavy duty loading conditions with 125mm - 150mm wide inner leaf.
To achieve loading figures, lintel must be laterally restrained.

5100



Keystone Lintels Ltd.
X/K-70 125 WIL
For extra heavy duty loading conditions with 125mm - 150mm wide inner leaf.
To achieve loading figures, lintel must be laterally restrained.

5400



Keystone Lintels Ltd.
X/K-70 125 WIL
For extra heavy duty loading conditions with 125mm - 150mm wide inner leaf.
To achieve loading figures, lintel must be laterally restrained.

5700



Keystone Lintels Ltd.
X/K-70 125 WIL
For extra heavy duty loading conditions with 125mm - 150mm wide inner leaf.
To achieve loading figures, lintel must be laterally restrained.

6000



Keystone Lintels Ltd.
X/K-70 125 WIL
For extra heavy duty loading conditions with 125mm - 150mm wide inner leaf.
To achieve loading figures, lintel must be laterally restrained.

6300



Keystone Lintels Ltd.
X/K-70 125 WIL
For extra heavy duty loading conditions with 125mm - 150mm wide inner leaf.
To achieve loading figures, lintel must be laterally restrained.

6600



Keystone Lintels Ltd.
X/K-70 125 WIL
For extra heavy duty loading conditions with 125mm - 150mm wide inner leaf.
To achieve loading figures, lintel must be laterally restrained.