



0600-3000

Keystone Lintels Ltd.
XK-90 WIL
For extra heavy duty loading
conditions with 140mm - 150mm
wide inner leaf.
To achieve loading figures, lintel
must be laterally restrained.




3150-4800

Keystone Lintels Ltd.
XK-90 WIL
For extra heavy duty loading
conditions with 140mm - 150mm
wide inner leaf.
To achieve loading figures, lintel
must be laterally restrained.




5100

Keystone Lintels Ltd.
XK-90 WIL
For extra heavy duty loading
conditions with 140mm - 150mm
wide inner leaf.
To achieve loading figures, lintel
must be laterally restrained.




5400

Keystone Lintels Ltd.
XK-90 WIL
For extra heavy duty loading
conditions with 140mm - 150mm
wide inner leaf.
To achieve loading figures, lintel
must be laterally restrained.




5700

Keystone Lintels Ltd.
XK-90 WIL
For extra heavy duty loading
conditions with 140mm - 150mm
wide inner leaf.
To achieve loading figures, lintel
must be laterally restrained.




6000

Keystone Lintels Ltd.
XK-90 WIL
For extra heavy duty loading
conditions with 140mm - 150mm
wide inner leaf.
To achieve loading figures, lintel
must be laterally restrained.



6300

Keystone Lintels Ltd.
XK-90 WIL
For extra heavy duty loading
conditions with 140mm - 150mm
wide inner leaf.
To achieve loading figures, lintel
must be laterally restrained.



6600

Keystone Lintels Ltd.
XK-90 WIL
For extra heavy duty loading
conditions with 140mm - 150mm
wide inner leaf.
To achieve loading figures, lintel
must be laterally restrained.