




Keystone Lintels Ltd.
X/K-90 125 WIL.
For extra heavy duty loading
conditions with 125mm - 150mm
wide inner leaf.
To achieve loading figures, lintel
must be laterally restrained.




Keystone Lintels Ltd.
X/K-90 125 WIL.
For extra heavy duty loading
conditions with 125mm - 150mm
wide inner leaf.
To achieve loading figures, lintel
must be laterally restrained.




Keystone Lintels Ltd.
X/K-90 125 WIL.
For extra heavy duty loading
conditions with 125mm - 150mm
wide inner leaf.
To achieve loading figures, lintel
must be laterally restrained.




Keystone Lintels Ltd.
X/K-90 125 WIL.
For extra heavy duty loading
conditions with 125mm - 150mm
wide inner leaf.
To achieve loading figures, lintel
must be laterally restrained.




Keystone Lintels Ltd.
X/K-90 125 WIL.
For extra heavy duty loading
conditions with 125mm - 150mm
wide inner leaf.
To achieve loading figures, lintel
must be laterally restrained.



Keystone Lintels Ltd.
X/K-90 125 WIL.
For extra heavy duty loading
conditions with 125mm - 150mm
wide inner leaf.
To achieve loading figures, lintel
must be laterally restrained.



Keystone Lintels Ltd.
X/K-90 125 WIL.
For extra heavy duty loading
conditions with 125mm - 150mm
wide inner leaf.
To achieve loading figures, lintel
must be laterally restrained.



Keystone Lintels Ltd.
X/K-90 125 WIL.
For extra heavy duty loading
conditions with 125mm - 150mm
wide inner leaf.
To achieve loading figures, lintel
must be laterally restrained.