



0600-1350




Keystone Lintels Ltd.
SK-90 215 WIL.
For standard loading conditions
with 215mm wide inner leaf as
a composite beam.
To achieve loading figures lintel
must be built in with blockwork as
shown.

1500-1650




Keystone Lintels Ltd.
SK-90 215 WIL.
For standard loading conditions
with 215mm wide inner leaf as
a composite beam.
To achieve loading figures lintel
must be built in with blockwork as
shown.

1800-2100




Keystone Lintels Ltd.
SK-90 215 WIL.
For standard loading conditions
with 215mm wide inner leaf as
a composite beam.
To achieve loading figures lintel
must be built in with blockwork as
shown.

2250-2400




Keystone Lintels Ltd.
SK-90 215 WIL.
For standard loading conditions
with 215mm wide inner leaf as
a composite beam.
To achieve loading figures lintel
must be built in with blockwork as
shown.

2550-2700




Keystone Lintels Ltd.
SK-90 215 WIL.
For standard loading conditions
with 215mm wide inner leaf as
a composite beam.
To achieve loading figures lintel
must be built in with blockwork as
shown.

2850-3000



Keystone Lintels Ltd.
SK-90 215 WIL.
For standard loading conditions
with 215mm wide inner leaf as
a composite beam.
To achieve loading figures lintel
must be built in with blockwork as
shown.

3150-4000



Keystone Lintels Ltd.
SK-90 215 WIL.
For standard loading conditions
with 215mm wide inner leaf as
a composite beam.
To achieve loading figures lintel
must be built in with blockwork as
shown.