




Keystone Lintels Ltd.
XK-K-150 215 WIL.
For extra heavy duty loading
conditions with 215mm wide
inner leaf.
To achieve loading figures, lintel
must be laterally restrained.




Keystone Lintels Ltd.
XK-K-150 215 WIL.
For extra heavy duty loading
conditions with 215mm wide
inner leaf.
To achieve loading figures, lintel
must be laterally restrained.




Keystone Lintels Ltd.
XK-K-150 215 WIL.
For extra heavy duty loading
conditions with 215mm wide
inner leaf.
To achieve loading figures, lintel
must be laterally restrained.




Keystone Lintels Ltd.
XK-K-150 215 WIL.
For extra heavy duty loading
conditions with 215mm wide
inner leaf.
To achieve loading figures, lintel
must be laterally restrained.




Keystone Lintels Ltd.
XK-K-150 215 WIL.
For extra heavy duty loading
conditions with 215mm wide
inner leaf.
To achieve loading figures, lintel
must be laterally restrained.



Keystone Lintels Ltd.
XK-K-150 215 WIL.
For extra heavy duty loading
conditions with 215mm wide
inner leaf.
To achieve loading figures, lintel
must be laterally restrained.



Keystone Lintels Ltd.
XK-K-150 215 WIL.
For extra heavy duty loading
conditions with 215mm wide
inner leaf.
To achieve loading figures, lintel
must be laterally restrained.



Keystone Lintels Ltd.
XK-K-150 215 WIL.
For extra heavy duty loading
conditions with 215mm wide
inner leaf.
To achieve loading figures, lintel
must be laterally restrained.