

Declaration of Performance

Product/DoP Ref: **S/K-90**

Old Ref: 003CPR2013 - Superseded

Product-type: **S/K-90**

Product intended to be used in walls and partitions

Manufacturer	Notified Body
Keystone Lintels Ltd, Ballyreagh Industrial Estate, Cookstown, Northern Ireland, BT80 9DG	Technical and Test Institute for Construction Prague, Prosecká 811/76A, 190 00 Praha 9-Prosek, Czech Republic
Keystone Lintels, in accordance with the Construction Products Regulations 2011 No. 305/2011 as amended, hereby declares that product type S/K-90 is manufactured to the requirements of the Harmonised European Standard EN 845-2: 2013 + A1: 2016.	TZUS No. 1020, conducted assessment of performance. The conformity of the product was determined as per the requirements stipulated in ZA.1 and ZA.2 of EN 845-2: 2013 + A1: 2016. The AVCP for the product is system 3.

Essential Characteristics		Lintel Length (mm)											hEN
		600-1200	1350-1500	1650-1800	1950-2100	2250-2400	2550-2700	2850-3000	3150-3600	3750-4000	4200	4350-4800	
Load Bearing Capacity (kN) Load Ratio 3:1	Figures shown are safe working loads	12	16	19	21	23	27	27	27	26	27	27	EN 845-2: 2013 + A1: 2016
Load Bearing Capacity (kN) Load Ratio 19:1		10	13	16	17	18	22	20	20	19	22	22	
Deflection Under Load		Less than Effective Span/325 at maximum safe working load											
Mass Per Unit Area		NPD											
Water Absorption		Zero											
Thermal Resistance (W/mk)		50 (Steel), 0.038 (EPS)											
Resistance to Fire		NPD (Contact Keystone Technical Department for information)											
Durability (against corrosion)		L14 (Lintel), L16.1 (Thermal Break Plate)											
Durability (against freeze/thaw)		Resistant											
Dangerous Substances		None											

Signed for on behalf of the manufacturer by:

Name: Derrick McFarland, Managing Director

At: Cookstown

On: 24 / 09 / 2025

Signature:

