

0600-1200



Keystone Lintels Ltd.
BOX/K-100
For standard loading conditions
to support internal openings.
Perforated steel for plaster key.

1350-1500



Keystone Lintels Ltd.
BOX/K-100
For standard loading conditions
to support internal or external
openings with 100mm wide wall
construction.
Perforated steel for plaster key.

1650-1800



Keystone Lintels Ltd.
BOX/K-100
For standard loading conditions
to support internal or external
openings with 100mm wide wall
construction.
Perforated steel for plaster key.

1950-2400



Keystone Lintels Ltd.
BOX/K-100
For standard loading conditions
to support internal or external
openings with 100mm wide wall
construction.
Perforated steel for plaster key.

2550-2700




Keystone Lintels Ltd.
BOX/K-100
For standard loading conditions
to support internal or external
openings with 100mm wide wall
construction.
Perforated steel for plaster key.

2850-3600




Keystone Lintels Ltd.
BOX/K-100
For standard loading conditions
to support internal or external
openings with 100mm wide wall
construction.
Perforated steel for plaster key.

3750-4200



Keystone Lintels Ltd.
BOX/K-100
For standard loading conditions
to support internal or external
openings with 100mm wide wall
construction.
Perforated steel for plaster key.

4350-4800



Keystone Lintels Ltd.
BOX/K-100
For standard loading conditions
to support internal or external
openings with 100mm wide wall
construction.
Perforated steel for plaster key.