



0600-1800




Keystone Lintels Ltd.
BOX/K-200
For standard loading conditions
to support internal or external
openings with 215mm wide wall
construction.
Perforated steel for plaster key.

1950-2100




Keystone Lintels Ltd.
BOX/K-200
For standard loading conditions
to support internal or external
openings with 215mm wide wall
construction.
Perforated steel for plaster key.

2250-2400




Keystone Lintels Ltd.
BOX/K-200
For standard loading conditions
to support internal or external
openings with 215mm wide wall
construction.
Perforated steel for plaster key.

2550-2700




Keystone Lintels Ltd.
BOX/K-200
For standard loading conditions
to support internal or external
openings with 215mm wide wall
construction.
Perforated steel for plaster key.

2850-3600




Keystone Lintels Ltd.
BOX/K-200
For standard loading conditions
to support internal or external
openings with 215mm wide wall
construction.
Perforated steel for plaster key.

3750-4200



Keystone Lintels Ltd.
BOX/K-200
For standard loading conditions
to support internal or external
openings with 215mm wide wall
construction.
Perforated steel for plaster key.

4350-4800



Keystone Lintels Ltd.
BOX/K-200
For standard loading conditions
to support internal or external
openings with 215mm wide wall
construction.
Perforated steel for plaster key.