

Declaration of Performance

DoP Ref: 010CPR2013

Product-type: HD/K-110


Product intended to be used in walls and partitions

Manufacturer	Notified Body
Keystone Lintels Ltd., Ballyreagh Business Park, Cookstown, Northern Ireland, BT80 9DG	Ceram, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ
Keystone Lintels, in accordance with the Construction Products Regulation (EU) No. 305/2011, hereby declares that product type <i>HD/K-110</i> is manufactured to the requirements of the Harmonised European Standard EN 845-2: 2003.	Ceram No. 1289, conducted determination of the product –type. The conformity of the product was determined as per the requirements stipulated in ZA.2 and ZA.3 of EN 845-2: 2003. The AVCP for the product is system 3.

Essential characteristics		Lintel length (mm)					hEN
		0600-1500	1650-2100	2250-3000	3150-3600	3750-4000	
Load Bearing Capacity (kN) <i>Load Ratio 3:1</i>	Figures shown are safe working loads	30	30	35	32	30	EN 845-2: 2003
Load Bearing Capacity (kN) <i>Load Ratio 19:1</i>		20	22	30	28	26	
Deflection Under Load	Less than Effective Span/325 at maximum safe working load						
Mass Per Unit Area	NPD						
Water Absorption	Zero						
Thermal Resistance (W/mK)	50 (steel), 0.038(EPS)						
Resistance to Fire	NPD (Contact Keystone Technical Department for information)						
Durability (against corrosion)	L14 (Lintel), L16.1 (Thermal Break Plate)						
Durability (against freeze/thaw)	Resistant						
Dangerous Substances	None						

Date: 30/06/2015

Issued under the sole responsibility of Keystone Lintels, signed by:



(Managing Director)