

## Declaration of Performance

Revision 2

Product/DoP Ref: 050CPR2013

Product-type: S/K-70 WIL

*Product intended to be used in walls and partitions*

Manufacturer	Notified Body
Keystone Lintels Ltd., Ballyreagh Business Park, Cookstown, Northern Ireland, BT80 9DG	Ceram, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ
Keystone Lintels, in accordance with the Construction Products Regulation (EU) No. 305/2011, hereby declares that product type S/K-70 WIL is manufactured to the requirements of the Harmonised European Standard EN 845-2: 2003.	Ceram No. 1289, conducted determination of the product-type.  The conformity of the product was determined as per the requirements stipulated in ZA.2 and ZA.3 of EN 845-2: 2003.  The AVCP for the product is system 3.

Essential Characteristics	Lintel Length (mm)									hEN
	0600-1350	1500-1650	1800	1950-2100	2250-2400	2550-3000	3150-3600	3750-4000	4200	
Load Bearing Capacity (kN) Load Ratio 3:1	12	13	20	19	24	27	30	27	26	EN 845-2: 2003
Load Bearing Capacity (kN) Load Ratio 19:1	10	11	17	17	20	21	26	25	22	
Deflection Under Load	Less than Effective Span/325 at maximum safe working load									
Mass Per Unit Area	NPD									
Water Absorption	Zero									
Thermal Resistance (W/mk)	50 (steel), 0.039 (RNO)									
Resistance to Fire	NPD (Contact Keystone Technical Department for information)									
Durability (against corrosion)	L14 (Lintel), L16.1 (Thermal Break Plate)									
Durability (against freeze/thaw)	Resistant									
Dangerous Substances	None									

**Signed for on behalf of the manufacturer by:**

**Name:** Derrick McFarland, Managing Director

**At:** Cookstown

**On:** 30 / 06 / 2015

**Signature:**

