

Declaration of Performance

Revision 2

Product/DoP Ref: 002CPR2013

Product-type: S/K-70

Product intended to be used in walls and partitions

Manufacturer	Notified Body
Keystone Lintels Ltd., Ballyreagh Business Park, Cookstown, Northern Ireland, BT80 9DG	Ceram, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ
Keystone Lintels, in accordance with the Construction Products Regulation (EU) No. 305/2011, hereby declares that product type S/K-70 is manufactured to the requirements of the Harmonised European Standard EN 845-2: 2003.	Ceram No. 1289, conducted determination of the product-type. The conformity of the product was determined as per the requirements stipulated in ZA.2 and ZA.3 of EN 845-2: 2003. The AVCP for the product is system 3.

Essential Characteristics	Lintel Length (mm)									hEN
	0600-1200	1350-1500	1650-1800	1950-2100	2250-2400	2550-3000	3150-3600	3750-4000	4200-4800	
Load Bearing Capacity (kN) Load Ratio 3:1	12	14	18	21	21	27	27	26	27	EN 845-2: 2003
Load Bearing Capacity (kN) Load Ratio 19:1	10	12	14	17	19	22	20	19	22	
Deflection Under Load	Less than Effective Span/325 at maximum safe working load									
Mass Per Unit Area	NPD									
Water Absorption	Zero									
Thermal Resistance (W/mk)	50 (steel), 0.039 (RNO)									
Resistance to Fire	NPD (Contact Keystone Technical Department for information)									
Durability (against corrosion)	L14 (Lintel), L16.1 (Thermal Break Plate)									
Durability (against freeze/thaw)	Resistant									
Dangerous Substances	None									

Signed for on behalf of the manufacturer by:

Name: Derrick McFarland, Managing Director

At: Cookstown

On: 30 / 06 / 2015

Signature:

