

## **Declaration of Performance**

Product/DoP Ref: 027CPR2013 Product-type: BOX/K-150

Product intended to be used in walls and partitions

Manufacturer	Notified Body				
Keystone Lintels Ltd, Ballyreagh Industrial Estate, Cookstown, Northern Ireland, BT80 9DG	Technical and Test Institute for Construction Prague, Prosecká 811/76A, 190 00 Praha 9-Prosek, Czech Republic				
Keystone Lintels, in accordance with the Construction Products Regulation (EU) No. 305/2011, hereby declares that product type BOX/K-150 is manufactured to the requirements of the Harmonised European Standard EN 845-2-2013+A1-2016.	TZUS No. 1020, conducted assessment of performance.  The conformity of the product was determined as per the requirements stipulated in ZA.1 and ZA.2 of EN 845-2-2013+A1-2016.  The AVCP for the product is system 3.				

Essential Characteristics		Lintel Length (mm)							
		0600- 1800	1950- 2100	2250- 2400	2550- 2700	2850- 3600	3750- 4200	4350- 4800	hEN
Load Bearing Capacity (kN) Total UDL	Figures shown are safe working loads	18	30	25	20	35	30	25	
Deflection Und	er Load	Less than Effective Span/325 at maximum safe working load							
Mass Per Unit Area		NPD						1-2016	
Water Absorption		Zero							2013+A
Thermal Resistance (W/mk)		50							EN 845-2-2013+A1-2016
Resistance t	NPD (Contact Keystone Technical Department for information)						Ш		
Durability (against corrosion)		L16.1							
Durabilit (against freezo	•	Resistant							
Dangerous Substances None									

## Signed for on behalf of the manufacturer by:

Name: Derrick McFarland, Managing Director

**At:** Cookstown **On:** 30 / 09 / 2022

Signature: