

Declaration of Performance

Product/DoP Ref: 032CPR2013

Product-type: SB/K

Product intended to be used in walls and partitions

Manufacturer	Notified Body
Keystone Lintels Ltd, Ballyreagh Industrial Estate, Cookstown, Northern Ireland, BT80 9DG	Technical and Test Institute for Construction Prague, Prosecká 811/76A, 190 00 Praha 9-Prosek, Czech Republic
Keystone Lintels, in accordance with the Construction Products Regulation (EU) No. 305/2011, hereby declares that product type SB/K is manufactured to the requirements of the Harmonised European Standard EN 845-2-2013+A1-2016.	TZUS No. 1020, conducted assessment of performance. The conformity of the product was determined as per the requirements stipulated in ZA.1 and ZA.2 of EN 845-2-2013+A1-2016. The AVCP for the product is system 3.

Essential Characteristics		Lintel Length (mm)						hEN
		0600-0900	1050-1200	1350-1500	1650-1800	1950-2250	2400-2700	
Load Bearing Capacity (kN) Total UDL	Figures shown are safe working loads	2.5	4	5	7	7	8	EN 845-2-2013+A1-2016
Deflection Under Load	Less than Effective Span/325 at maximum safe working load							
Mass Per Unit Area	NPD							
Water Absorption	Zero							
Thermal Resistance (W/mk)	50							
Resistance to Fire	NPD (Contact Keystone Technical Department for information)							
Durability (against corrosion)	L14							
Durability (against freeze/thaw)	Resistant							
Dangerous Substances	None							

Signed for on behalf of the manufacturer by:
Name: Derrick McFarland, Managing Director

At: Cookstown

On: 30 / 09 / 2022

Signature:
