

## **Declaration of Performance**

Product/DoP Ref: 026CPR2013 Product-type: BOX/K-100

Product intended to be used in walls and partitions

Manufacturer	Notified Body				
Keystone Lintels Ltd, Ballyreagh Industrial Estate, Cookstown, Northern Ireland, BT80 9DG	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ				
Keystone Lintels, in accordance with the Construction Products (Amendment etc.) (EU Exit) Regulations 2020 No. 1359, hereby declares that product type BOX/K-100 is manufactured to the requirements of the Harmonised European Standard EN 845-2-2013+A1-2016.	Lucideon Ltd No. 0013, conducted assessment of performance.  The conformity of the product was determined as per the requirements stipulated in ZA.1 and ZA.2 of EN 845-2-2013+A1-2016.  The AVCP for the product is system 3.				

Essential Characteristics		Lintel Length (mm)								
		0600- 1200	1350- 1500	1650- 1800	1950- 2400	2550- 2700	2850- 3600	3750- 4200	4350- 4800	hEN
Load Bearing Capacity (kN) Total UDL	Figures shown are safe working loads	15	15	18	25	20	35	30	24	
Deflection Und	er Load	Less than Effective Span/325 at maximum safe working load								
Mass Per Unit Area		NPD								1-2016
Water Absorption		Zero								2013+A
Thermal Resistance (W/mk)		50								EN 845-2-2013+A1-2016
Resistance to Fire		NPD (Contact Keystone Technical Department for information)								Ш
Durability (against corrosion)		L16.1								
Durabilit (against freez	Resistant									
Dangerous Sul	None									

## Signed for on behalf of the manufacturer by:

Name: Derrick McFarland, Managing Director

**At:** Cookstown **On:** 14 / 10 / 2022

Signature: