

Declaration of Performance

Product/DoP Ref: 043CPR2013

Product-type: HD/K-110 WIL

Product intended to be used in walls and partitions

Manufacturer	Notified Body
Keystone Lintels Ltd, Ballyreagh Industrial Estate, Cookstown, Northern Ireland, BT80 9DG	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ
Keystone Lintels, in accordance with the Construction Products (Amendment etc.) (EU Exit) Regulations 2020 No. 1359, hereby declares that product type HD/K-110 WIL is manufactured to the requirements of the Harmonised European Standard EN 845-2-2013+A1-2016.	Lucideon Ltd No. 0013, conducted assessment of performance. The conformity of the product was determined as per the requirements stipulated in ZA.1 and ZA.2 of EN 845-2-2013+A1-2016. The AVCP for the product is system 3.

Essential Characteristics	Lintel Length (mm)				hEN
	0600-1350	1500-1800	1950-2100	2250-2700	
Load Bearing Capacity (kN) Load Ratio 3:1	20	30	30	36	EN 845-2-2013+A1-2016
Load Bearing Capacity (kN) Load Ratio 19:1	17	25	25	32	
Deflection Under Load	Less than Effective Span/325 at maximum safe working load				
Mass Per Unit Area	NPD				
Water Absorption	Zero				
Thermal Resistance (W/mk)	50 (steel), 0.039 (EPS)				
Resistance to Fire	NPD (Contact Keystone Technical Department for information)				
Durability (against corrosion)	L14 (Lintel), L16.1 (Thermal Break Plate)				
Durability (against freeze/thaw)	Resistant				
Dangerous Substances	None				

Signed for on behalf of the manufacturer by:

Name: Derrick McFarland, Managing Director

At: Cookstown

On: 14 / 10 / 2022

Signature:

